

**PRODUCT INFORMATION SHEET**  
**ULTRAPRIME**  
**MOISTURE CURE CONCRETE SEALER**  
**For use with 5000 and 6000 Series Products**

**DESCRIPTION:**

ULTRAPRIME is a single component penetrating moisture cure concrete sealer used with 5000 and 6000 products.

**SUPPLEMENTAL PRODUCTS:**

All 5000 or 6000 flooring, lining, grout, and coating products.

**PACKAGING AND COVERAGE:**

ULTRAPRIME is packaged in 2 gallon or 5 gallon pails. Each two gallon kit will cover approximately 500 sq. ft. at 6 mils wet (3 mils DFT), depending on porosity of the concrete.

**PREPARATION:**

See Installation Instruction Sheet for finish system to be installed.

**MIXING:**

No mixing is required because ULTRAPRIME is a single component product.

**APPLICATION:**

Apply ULTRAPRIME to the substrate surface with a roller in at approximately 6 mils wet (2 to 3 mils DFT). Make sure to wet entire surface, but do not allow ULTRAPRIME to puddle. Coverage will be approximately 250 sq. ft. per gallon at 6 mils wet (3 mils DFT). Working life of open container is 6-8 hours. Only apply ULTRAPRIME to surfaces you intend to lay within 6 hours. If left longer, the surface must be sanded or scarified.

**CURE TIME:**

ULTRAPRIME will cure for application of finish product within 45 minutes at 75<sup>0</sup> F (24<sup>0</sup> C). Surface will be tacky when it is ready to be top-coated.

**CLEANUP:**

Cured or hardened ULTRAPRIME will bond to practically all surfaces and is extremely difficult to remove. Clean all tools immediately after use with acetone or other solvent based cleaners.

**SAFETY:**

Avoid skin contact. If eye contact occurs, flush with water and consult a physician immediately. Keep work areas well ventilated. Never seal a container as the continuing exothermic reaction may cause container to explode. ULTRAPRIME is manufactured using a solvent which will give off an odor during application. Customer is responsible for protecting employees and food products from these odors. Cured product poses no threat of odor contamination. ULTRAPRIME Material Safety Data Sheets are available upon request.

**IMPORTANT NOTICE TO PURCHASER:**

**The following is made in lieu of all warranties, expressed or implied. Seller and manufacturer's only obligation shall be to replace such quantities of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential arising out of the use of or inability to use the product. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risks and liability whatsoever in connection therewith. The foregoing may not be altered unless written authorization is received from PROTECTIVE FLOORINGS AND LININGS, INC.**